

## High Quality 4 Colour Direct-to-Garment Printer

Discover Mutoh's all new ValueJet 404GT direct-to-garment inkjet printer. Engineered & manufactured in Japan, the VJ-404GT offers CMYK printing possibilities for the digital production of white or light coloured garments. Mutoh's Oeko-Tex® compliant water-based pigmented textile inks will allow you to produce vibrant colours with excellent ink density on a variety of garments. Offering a printable area of 420 mm x 576 mm, the VJ-404GT printer is equipped with four piezo drop-on-demand print heads, producing print resolutions up to 1200 x 1200 dpi.

Compact & robustly built, the 404GT can be equipped with different sizes of easily interchangeable print platens (S, M, L). A 7 inch LCD touch screen display allows you to easily & swiftly operate the printer. The standard printer installer & driver software for Windows, as well as a Mutoh proprietary "layout & print" software tool facilitates quick & easy operation. T-shirt printing fun starts with Mutoh's ValueJet 404GT!

### **Product Highlights**

- Compact printer, engineered & manufactured in Japan
- CMYK Oeko-Tex® compliant water-based pigmented textile inks
- Automatic Garment Collision Detection
- Wide print area: 420 mm x 576 mm!
- Extreme print quality up to 1200x1200 dpi
- Vibrant colours & excellent ink density
- Easy & clickable print tables up to L size
- User-friendly design with 7 inch LCD touch screen display

#### **Application Possibilities**

The VJ-404GT is specifically targeted at fashion designers, promotional garment printers, online web shop businesses as well as screen printers and is suited for sampling, customised one-off prints as well as short-run production of t-shirts, canvas bags, shoes, caps, etc..









# High Quality 4 Colour Direct-to-Garment Printer | SPECIFICATIONS

#### Technical Key Specifications

Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Heads	4
Nozzle Configuration	384 nozzles (192 x 2 lines) per head
Resolutions	600 x 600 dpi , 600 x 1200 dpi, 1200 x 1200 dpi
Head-Garment Collision D	Detection Optical sensor

Max. Size Print Table	428 x 600 mm	
Max. Print Area	420 x 576 mm	
Table Height Adjustment	15 mm	
Print Jig Accommodation	Height: max. 155 mm / Weight: max 7 kg	
Print Tables - Sizes Tabl	e L 405 x 585 mm (Printable: 380 x 560 mm)	)
Tabl	e M 335 x 485 mm (Printable: 310 x 460 mm)	
Tabl	e S 255 x 355 mm (Printable: 230 x 330 mm)	

#### Productivity VJ-404GT

Resolution	VJ-404 GT CMYK Output
1200 x 1200 dpi	36 t-shirts per hour
600 x 1200 dpi	60 t-shirts per hour
600 x 600 dpi	120 t-shirts per hour

The indicated number of printed T-shirts per hour is based on the output of an A4-size (297 mm x 210 mm) image. The calculated production time excludes data processing and garment mounting/unmounting times.

#### Inks and Pre-Treatment Specifications

Ink Type	Water-based pigmented direct textile inks Oeko-Tex® compliant	
Ink Volume	200 ml cassettes	
Ink Colours	CMYK	
Printable Substrates	Light garments, 100% cotton, 100% PES, cotton/polyester mixed fibre fabrics with minimum 50% cotton	
Pre-Treatment Liquids Pre-treatment liquid for cotton for improved sharpness and fastness results		
	Pre-treatment liquid for printing onto 100% white or light coloured PES	
Garment Handling	Thickness	Up to 155 mm (including mounting jig)
	Weight	Up to 2 kg (including platen)

#### Operation Info

Operation into	
Display	7 inch (156.7 x 89.1 mm) LCD touch screen
Connectivity	LAN (10/100BASE-T)
Required Operating System	Windows Vista, 7, 8 and up
Software	Mutoh Proprietary Layout and Print Tool
Supported File Types	BMP, JPEG, TIFF, PNG

#### Media Specifications

Wedia openioations		
Max. Size Print Table	428 x 600 mm	
Max. Print Area	420 x 576 mm	
Table Height Adjustment	15 mm	
Print Jig Accommodation	Height: max. 155 mm / Weight: max 7 kg	
Print Tables - Sizes Table	e L 405 x 585 mm (Printable: 380 x 560 mm)	
Table	e M 335 x 485 mm (Printable: 310 x 460 mm)	

in Stand-by	≤ 29 W
In Sleep Mode	≤ 17 W
Power Supply	AC 200-240 - 50 Hz
Noise	Printing 58 2dB / Standby 33 1dB

≤ 130 W

#### Recommended Working Environment

Temperature	22 °C - 30 °C with Δt: max. 2 °C/h
Humidity	40 % - 60 % (no condensation)
	with ∆RH: max. 5% RH/h

#### Machine Measurements

**Power Consumption** During Printing

Width x Depth x Height	817 x 1425 x 488 mm
Weight	82 kg